

MATERIAL SAFETY DATA SHEET

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **Majestic Stone Polish Protector**
DOT Ship Description: CONSUMER COMMODITY ORM-D

ID #: **MAJRPP45818**

PRODUCT USE/CLASS: Duster and Polish

MANUFACTURED FOR: M3 Technologies, Inc., 57 Lamberts Lane, Cohasset, MA 02025
PREPARER: Regulatory Department

PHONE: 800-342-4533
PREPARE DATE: 12-15-09
REVISION DATE: 06-22-11

EMERGENCY TELEPHONE: (CHEMTREC): 800-424-9300

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	% WT	313/CHEM	SKIN	CARCINOGEN	PEL	TLV-TWA
White Mineral Oil	8042-47-5	10 - 20	NO	NO	NO	5 mg/m3*	5 mg/m3*
Citrus Terpene	5989-27-5	1 - 10	NO	NO	NO	N/E	N/E
Liquefied Petroleum Gas	68476-86-8	10 - 20	NO	NO	NO	1000 ppm	1000 ppm

*exposure limits for mist

SECTION III - PHYSICAL DATA

AEROSOL CONCENTRATE:

BOILING RANGE: 212°F

pH: 11

APPEARANCE/ODOR: White Gel/Citrus Scent

SPECIFIC GRAVITY: (H₂O=1) @ 70°F: 0.96

SOLUBILITY IN H₂O: Complete

VAPOR DENSITY: (Air=1): >1

TOTAL CONTENTS:

TOTAL VOC %: 17.71%

VAPOR PRESSURE: (can; psig @72°F): 55

(See Section XI for abbreviation legend)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (CONC): None to Boiling (TOC)

FLAMMABILITY (as per CSMA Flame Projection Test): Flammable Spray

EXTINGUISHING MEDIA: Foam, CO₂, Dry Media

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperature above 120°F may cause bursting.

SECTION VI - REACTIVITY DATA

STABILITY: Material Stable

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents..

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide

SECTION VII - STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

NFPA CODE 30B RATING: Level 2 Aerosol

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120°F.

SECTION VIII - HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

EYES: May cause slight irritation.

SKIN: Frequent or prolonged skin contact may cause irritation. May aggravate existing skin conditions.

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects. Excessive inhalation of mist may lead to fibrosis and reduced pulmonary function.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis and delayed pulmonary edema.

FIRST AID PROCEDURES:

EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN: Wash with soap and water. If irritation persists seek medical attention.

INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

SECTION IX - SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.

VENTILATION: Provide local exhaust to keep air concentrations of ingredients listed in Section II below established exposure limits.

PROTECTIVE GLOVES: Use chemical resistant gloves if hand contact will be made.

EYE PROTECTION: always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION X – SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

SECTION XI - HMIS RATINGS

HMIS RATING (Based on Aerosol Conc.): 0-Minimal 1-Slight 2-Moderate 3-Serious 4-Extreme

Health: 1

Flammability: 1

Reactivity: 0

Personal Protection: B

SECTION XII – OTHER INFORMATION

Disclaimer: No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose, or any other nature, is made with respect to information concerning the product referred to in this document. The information contained herein is to the best of our knowledge and believe accurate. However, since the conditions of handling and use are beyond our control, it is impossible to foresee every health effect or exposure risk incurred by the used of this product. All chemical present unknown health hazards and should be used with caution. The information and recommendations contained herein are presented in good faith and are supplied pursuant to 29 CFR 1910.1200. The user should review this information in conjunction with their knowledge of the application intended to determine the suitability of this product for such purpose. In no event will the supplier be responsible for any damage so any nature whatsoever, resulting from the use, reliance upon, or the misuse of this information. Further, it is the direct responsibility of the user to comply with all applicable Federal, state and local regulations governing the use and disposal of this material.

NE = Not Established

NA = Not Applicable

ND = Not Determined

< = Less than

> = More than