

Majestic Low Odor Solvent Based Sealer



Majestic Low Odor Solvent Based Impregnating Sealer is a penetrating sealer for all natural stone, grout, concrete and any other porous mineral or man-made material. It provides an invisible barrier, protecting your stone surfaces from water and oil born stains, while allowing the surface to properly breathe.

For Use On: All stone surfaces, interior and exterior, weather resistant. Will not alter the original color of most stones.

Available Sizes: Quart, case of 12 Quarts, Gallon, case of 4 Gallons

Coverage: 300-1,500 ft/gallon

Product Features:

- Provides an invisible barrier resistant to stains while allowing the surface to properly breathe
- Deeply penetrates the surface for maximum protection
- Protects your stone from water and oil born stains

THOROUGHLY TESTED

Directions:

Surface must be clean, dry and free of coatings or sealers. Clean/strip floor first with Majestic Deep Clean Stripper Degreaser. Test small area before application to insure desired results will be achieved. Protect all adjacent surfaces with film/plastic.

Large Floors: Use a floor machine with a white or red nylon pad. Start in an area 15-20 square feet. Apply product to middle of area, position nylon pad onto product, and with machine, spread over area. Keep rubbing it in until all product residue is removed. Repeat until whole floor has been treated. Discard the pad when it becomes too tacky. Product may require more than one application. On polished marble and hone-finished travertine one application will do. On granite, at least two applications are generally necessary. Very porous mercantile granites, sandstone, quartzite, etc. may require three or more applications.

Countertops: Apply product on stone surface spreading uniformly with clean white rag. Let product sit for 4 minutes allowing maximum penetration. When stone surface is almost dry, apply more product, rub any remaining residue off. Repeat until whole surface has been treated. Highly porous surfaces may require a second or third application to give full protection and achieve desired look. Wait a minimum of 1 hour between applications.

M3 Technologies, Inc.
57 Lamberts Lane
Cohasset, MA 02025
Toll Free: 800-342-4533
Fax: 781-383-3135
www.m3techinc.com

