

# Majestic Polymeric 3



Polymeric 3 contains a new generation polymer that is chemically programmed to migrate continually to the surface when used in high traffic areas. Polymeric 3 is a sealer and finish one product. It inhibits scratching and gives the floor an exceptionally long wear life so floors stay newer looking longer.

**For Use On:** All concrete, natural stone and resilient floors such as vinyl and linoleum.

**Available Sizes:** Gallon, case of 4 gallons, 5 gallon, 55 gallon

**Coverage:** Depending on the porosity of the floor surface, coverage will be between 800-1,200 sq. ft. per gallon.

**Product Features:**

- Creates a durable high gloss finish capable of withstanding heavy traffic
- Creates a water and chemical-resistant finish
- Can be used in outdoor applications

## THOROUGHLY TESTED

**Directions:**

Clear the area of all movable objects. Sweep the floor clean of loose dirt and rubbish. If the floor surface has previously been coated with a floor finish, it must be stripped and remove all old wax and floor finish. Care should be taken to insure that the unfinished surface is very clean and dry.

1. Rinse the floor as thoroughly as possible and let dry.
2. Work with clean equipment and apply a thin coat of product.
3. Allow to dry completely (a minimum of 2 hours) before applying another coat. Apply 1 to 2 coats allowing plenty of time between coats for drying. Do not resume traffic on the surface for at least 12 hours. Light foot traffic before that is fine, but no heavy cart or vehicle traffic.
4. Sweep daily with dust mop/cloth. Clean with neutral pH cleaner. Light cleaning will remove surface soils, stains and maintain gloss and color. Dry buff or burnish after cleaning to obtain a glossy look. Heavy traffic lanes may need to be maintained with a spray buff or restorer.

M3 Technologies, Inc.  
57 Lamberts Lane  
Cohasset, MA 02025  
Toll Free: 800-342-4533  
Fax: 781-383-3135  
www.m3techinc.com

